

FICHA TÉCNICA STACKER ELÉTRICO DUPLEX

Characteristics	Manufacturer	Unit	JAC
	Model		CDD15
	Power unit		electric
	Operation		pedestrian
	Rated traction weight	kg	1500
	Load center distance	mm	600
	Axle centre to fork face	mm	720
	Wheel base	mm	1167
Weights	Service weight (with battery)	kg	495
Wheels/Tyres	Tires		PU
	Driving wheel size	(mm)	210×70
	Bearing wheel size	(mm)	80×70
	additional wheels (dimensions)	(mm)	115×55
	Wheels, number front/rear (x = driven)		1x+1/4
	Track width	mm	522
	Track width	mm	410/535
Dimensions	The max. lifting height	mm	3000
	Load capacity on Max. height	kg	900
	Extended mast height	mm	3452
	Lowered mast height	mm	1995
	Free lifting height	mm	0
	Height of handle in drive position min./max.	mm	700/1225
	Lowered fork height	mm	86
	Overall length	mm	1740
	Length to fork face	mm	590
	Overall width	mm	795
	Fork dimensions	s/c/l (mm)	60/160/1150
	Width of forks	mm	570/695
	Min.Ground clearance	mm	26
	Aisle width with pallet 1000 x 1200 across forks	mm	2074
Aisle width with pallet 800 x 1200 along forks	mm	2040	
Min.Turning radius	mm	1342	
Performance	Travel speed, laden/unladen	km/h	4.0/4.2
	Lifting speed, with/without load	mm/s	92/136
	Lowering speed, with/without load	mm/s	112/98
	Maximum climbing ability, with/without load	%	6/8
	Service brake		electromagnetic braking
Drive	Drive motor, 60 minute rating	kW	0,75
	Lift motor rating at S3 15%	kW	2,2
	Battery according to DIN 43531/35/36 A,B,C,no		no
	Battery voltage	V/Ah	2×12/100 (Maintenance-free battery)
	Battery weight (± 5%)	kg	2×27
Others	Type of drive control		DC power
	Noise level at operator's ear	dB(A)	69
	Steering type		Mechanical steering